

# ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

## TDS of STANDARD SERIE YS9030AJ

Product	Product Category	Coating
PTFE GLASS FABRIC	STANDARD SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1500, 2000, 2600 mm	39.5, 59.1, 78.8, 102.4 inches
Thickness	0.30 mm	0.0118 inches
Coated weight	625 g/m <sup>2</sup>	18.43 oz/yd <sup>2</sup>
PTFE content	53%	53%
Tensile Stength	680 N/cm      Warp	389 lbs/inches      Warp
	640 N/cm      Fill	366 lbs/inches      Fill
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® offering PTFE fabric with easy release and high glossy coating, which also has super abrasion resistance, high mechanical strength and long lifetime.

0.30mm Teflon fiberglass is FDA & LFGB certificated, can be used in direct contact with food.

It is also widely used as a releasing sheet and laminating sheet for solar cell manufacturing, PVC or PE mold release, garment fusing, conveyor belt for paper industry, release & transport sheet for wood laminating, belting for food like Tortilla and so on.



ESONE® is a registered trademark owned by  
 Jiangsu Esone New Material Co.,Ltd  
 Taixing Youngsun FL-Plastics Co.,Ltd  
 Western End of South Third Ring Road, Taixing, Jiangsu, China  
 Tel: 0523-8759020    E-Mail: sales@chinayoungsun.com

[www.ptfe-fabrics.com](http://www.ptfe-fabrics.com)