

ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of TEAR RESISTANT SERIE YS9008AT

Product	Product Category	Coating
PTFE GLASS FABRIC	TEAR RESISTANT SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000 mm	39.5 inches
Thickness	0.075 mm	0.0030 inches
Coated weight	135 g/m ²	4 oz/yd ²
PTFE content	64%	64%
Tensile Stength	190 N/cm Warp	109 lbs/inches Warp
	180 N/cm Fill	103 lbs/inches Fill
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® Tear Resistant Series PTFE coated fiberglass fabric, has easy release surface, and extra high tensile strength and tear strength.

Applications of PTFE coated fiberglass include release sheet for heat press machines, belting for food industry, Non stick baking liner or oven liner, electrical insulation and industrial processing.

Teflon fiberglass is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by
 Jiangsu Eson New Material Co.,Ltd
 Taixing Youngsun FL-Plastics Co.,Ltd
 Western End of South Third Ring Road, Taixing, Jiangsu, China
 Tel: 0523-8759020 E-Mail: sales@chinayoungsun.com

www.ptfe-fabrics.com