

# ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

## TDS of INDUSTRIAL SERIE YS9020A-1

Product	Product Category	Coating
PTFE GLASS FABRIC	INDUSTRIAL SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1250, 1500, 1900 mm	39.5, 49.3, 59, 74.8 inches
Thickness	0.20 mm	0.0079 inches
Coated weight	350 g/m <sup>2</sup>	10.32 oz/yd <sup>2</sup>
PTFE content	43%	43%
Tensile Stength	460 N/cm Warp	263 lbs/inches Warp
	410 N/cm Fill	234 lbs/inches Fill
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® Industrial Series offering good release coating with medium PTFE content, which also has good abrasion resistance and enough tensile strength.

Applications of PTFE coated fiberglass include release sheet for heat press machines, belting for food industry, Non stick baking liner or oven liner, electrical insulation and industrial processing.

Teflon fiberglass is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by  
 Jiangsu Eson New Material Co.,Ltd  
 Taixing Youngsun FL-Plastics Co.,Ltd  
 Western End of South Third Ring Road, Taixing, Jiangsu, China  
 Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com

[www.ptfe-fabrics.com](http://www.ptfe-fabrics.com)