


ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of ARAMID/GLASS SERIE YS6007



Product	Product Category	Coating
PTFE KEVLAR/GLASS FABRIC	ARAMID/GLASS SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1700, 2000, 2700, 3400, 4000 mm	39.5, 67, 81, 98.4, 110, 126, 132, 142, 158 inches
Mesh Size	4 x 4 mm	0.1575 x 0.1575 mm
Warp	Kevlar	Kevlar
Weft	Fiberglass	Fiberglass
Tensile Strength	380 N/cm Warp	217 lbs/inches Warp
	900 N/cm Fill	514 lbs/inches Fill
Color	Brown	Brown
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® Kevlar/Glass series is woven by fiberglass and aramid fabric (like Kevlar) or Nomax. The main applications is screen printing, drying industry, packaging industry, textile industry, food processing industry, laminated glass manufacturing, wood processing industry and so on, which is used as heat resistant and non stick conveyor belt to transport materials through ovens, or used as release sheet in heat. 4x4mm PTFE open mesh fabric is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by
 Jiangsu Eson New Material Co.,Ltd
 Taixing Youngsun FL-Plastics Co.,Ltd
 Western End of South Third Ring Road, Taixing, Jiangsu, China
 Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com