


# ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

## TDS of STRONGER FIBERGLASS SERIE YS6031



Product	Product Category	Coating
PTFE GLASS FABRIC	STRONGER FIBERGLASS SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1500, 2050, 2700, 3200, 3600, 3800, 4000 mm	39.5, 59, 81, 106, 134, 142, 150, 158 inches
Mesh Size	2 x 2 mm	0.0787 x 0.0787 inches
Weight	660 g/m <sup>2</sup>	19.5 oz/yd <sup>2</sup>
Weft	Triple weft	Triple weft
Warp	Triple warp	Triple warp
Tensile Strength	680 N/cm Warp	389 lbs/inches Warp
	620 N/cm Fill	354 lbs/inches Fill
Color	Black	Black
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® Triple weft PTFE mesh fabric has very strong tensile strength, is the excellent belting material and PTFE architecture membrane material.

The main applications is screen printing, drying, packaging industry, textile industry, wood processing industry and so on, which is used as heat resistant and non stick conveyor belt to transport materials through ovens. 4x4 mm PTFE open mesh fabric is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by  
 Jiangsu Eson New Material Co.,Ltd  
 Taixing Youngsun FL-Plastics Co.,Ltd  
 Western End of South Third Ring Road, Taixing, Jiangsu, China  
 Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com

[www.ptfe-fabrics.com](http://www.ptfe-fabrics.com)