



PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of PTFE FILM ADHESIVE SERIES YS7913AJY

Product	Product Category	Coating
PTFE SKIVED FILM ADHESIVE TAPE	PTFE FILM ADHESIVE SERIE	ACRYLIC PRESSURE SENSITIVE ADHESIVE

Properties	Metric	Imperial
Standard width Please ask for other widths	5 - 500 mm	0.2 - 19.7 inches
Backing Thickness PTFE Film	0.09 mm	0.0035 inches
Total Thickness PTFE Film and Acrylic PSA	0.13 mm	0.0051 inches
Adhesion	4.5 N/cm	40 oz/inches
Color	White or Gray	White or Gray
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® Skived PTFE Film Adhesive Tape is manufactured from the highest quality virgin PTFE resins, and is designed to meet the requirement of most electrical, mechanical and industrial applications. Once the PTFE Film been skived from PTFE resins, it will be chemically treated or etched, which will remove the fluorine surface by creating a new sodium surface. Then the heat resistant adhesive will be allowed to bond PTFE film, resulting in Teflon Skived Film with Acrylic Adhesive.



ESONE® is a registered trademark owned by
Jiangsu Esone New Material Co.,Ltd
Taixing Youngsun FL-Plastics Co.,Ltd
Western End of South Third Ring Road, Taixing, Jiangsu, China
Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com

www.ptfe-fabrics.com