



PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of FLUORIN COATED SERIES YS9038HS(ELASTIC)

Product	Product Category	Coating
ANTI STATIC PTFE IMPREGNATED FABRIC	FLUORIN COATED SERIES	FLUORIN(PTFE)

Properties	Metric	Imperial
Basic Fabric	Satin weaved fiberglass	
Coating	One side	
Surface resistance	10 ⁷ to 10 ⁴ OHMS/m ²	
Standard width Please ask for other widths	1500 mm	60 inches
Coated Weight	550 g/m ²	16.2 oz/yd ²
Thickness	0.38 mm	0.016 inches
Tensile strength	Warp 2150 N/5cm	246 lbs/inches
	Fill 1750 N/5cm	200 lbs/inches
Mullen Burst	455 N/cm ²	650 psi
Flame Resistant	Char Length 2.54 cm max	Char Length 1 inch max
	Afterglow 1 second max	Afterglow 1 second max
	Flame Out 1 second max	Flame Out 1 second max
Temperature resistance	-73 to +315 °C	-100 to +600 °F
UV Resistance	1000 hours; no change in tensile	
Color	Black	

ESONE® Fluorin Coated Series is using Satin weaved fiberglass fabric, coated with Fluorin(special formulated PTFE) on one side or both side.

And ESONE YS9038HS elastic style has **extra high elastic flexible and soft property**.

It has high tensile strength, is UV resistant and Flame resistant. The color can be Gray, white, yellow, black, red or other colors.

Applications of Fluorin coated series include wrapping insulation for pumps, filters, exchange, pipeline, valves, freeze protection and so on, it's wrapped outside the insulation blanket, as this fabric is anti-aging, anti-chemical and anti-environment. Different color is used for different application, such as steam pipeline, oil pipeline or gas pipeline.



ESONE® is a registered trademark owned by
Jiangsu Eson New Material Co.,Ltd
Taixing Youngsun FL-Plastics Co.,Ltd
Western End of South Third Ring Road, Taixing, Jiangsu, China
Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com

www.ptfe-fabrics.com