



PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of PREMIUM SERIE YS9008AJ-PM

Product	Product Category	Coating
PTFE GLASS FABRIC	PREMIUM SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1250 mm	39.5, 49.3 inches
Thickness	0.08 mm	0.0031 inches
Coated weight	165 g/m ²	4.87 oz/yd ²
PTFE content	71%	71%
Tensile Stength	130 N/cm Warp	74.23 lbs/inches Warp
	110 N/cm Fill	62.81 lbs/inches Fill
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® offering excellent smooth and high gloss surface coating, which has also super abrasion resistance and high tensile strength.

Applications of PTFE coated fiberglass include release sheet for heat press machines, belting for food industry, Non stick baking liner or oven liner, electrical insulation and industrial processing.

0.08mm Teflon fiberglass is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by
Jiangsu Eson New Material Co.,Ltd
Taixing Youngsun FL-Plastics Co.,Ltd
Western End of South Third Ring Road, Taixing, Jiangsu, China
Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com

www.ptfe-fabrics.com