



PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of TEAR RESISTANT SERIE YS9025AT

Product	Product Category	Coating
PTFE GLASS FABRIC	TEAR RESISTANT SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000,1250,1500 mm	39.5, 49.3,59.1inches
Thickness	0.25 mm	0.0098 inches
Coated weight	520 g/m ²	15.34 oz/yd ²
PTFE content	62%	62%
Tensile Stength	580 N/cm Warp	331 lbs/inches Warp
	550 N/cm Fill	314 lbs/inches Fill
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® Tear Resistant Series PTFE coated fiberglass fabric, has easy release surface, and extra high tensile strength and tear strength.

Applications of PTFE coated fiberglass include release sheet for heat press machines, belting for food industry, Non stick baking liner or oven liner, electrical insulation and industrial processing.

Teflon fiberglass is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by
Jiangsu Eson New Material Co.,Ltd
Taixing Youngsun FL-Plastics Co.,Ltd
Western End of South Third Ring Road, Taixing, Jiangsu, China
Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com

www.ptfe-fabrics.com